

Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition	Errors
1	IS&R L1	3688	((385/123) or (385/124) or (385/126) or (385/127)).CCLS.	USPAT; US-PGPUB; EPO; JPO	2004/ 07/05 11:04			0
2	BRS L2	549	1 and ((negative near2 dispersion) or dcf or (dispersion near2 (compensating or compensation) near2 (fiber or fibre)))	USPAT; US-PGPUB; EPO; JPO	2004/ 07/05 11:06			0
3	BRS L3	777	((negative near2 dispersion) or (dispersion near2 (compensating or compensation))) near3 (fiber or fibre or fibers or fibres).tl,ab.	USPAT; US-PGPUB; EPO; JPO	2004/ 07/05 11:08			0
4	BRS L4	190	(2 or 3) and (pmd or ((polarization or polarisation) adj mode adj dispersion))	USPAT; US-PGPUB; EPO; JPO	2004/ 07/05 11:09			0
5	BRS L5	130	4 and ((transmission or bend or bending or microbending) near3 (loss or attenuation))	USPAT; US-PGPUB; EPO; JPO	2004/ 07/05 11:10			0
6	BRS L6	65	4 and (mfd or (mode adj field adj diameter))	USPAT; US-PGPUB; EPO; JPO	2004/ 07/05 11:10			0
7	BRS L7	190	4 or 5 or 6	USPAT; US-PGPUB; EPO; JPO	2004/ 07/05 11:10			0

10/781719